

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 773 648 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
25.05.2005 Bulletin 2005/21

(51) Int Cl.7: **H04L 12/18, H04Q 11/04**

(21) Application number: **95203016.1**

(22) Date of filing: **07.11.1995**

(54) Method and apparatus for managing multicast connections

Verfahren und Einrichtung zur Verwaltung von Mehrfachverbindungen

Méthode et appareil pour la gestion de connexions à destination multiples

(84) Designated Contracting States:
BE DE ES FR GB IT SE

(43) Date of publication of application:
14.05.1997 Bulletin 1997/20

(73) Proprietor: **ALCATEL**
75008 Paris (FR)

(72) Inventors:
• **Pauwels, Ludwig Alice Julienne**
B-9120 Beveren (BE)
• **Lefebvre, Pascal Albert Emile**
B-1150 Brussels (BE)

(74) Representative:
Narmon, Gisèle Marie Thérèse et al
Alcatel Bell N.V.
Intellectual Property Department
Francis Wellesplein 1
2018 Antwerpen (BE)

(56) References cited:
US-A- 4 813 038 **US-A- 5 303 233**

• **IEEE GLOBECOM 93, vol. 1, 29 November 1993,**
TX, US, pages 34-41, XP000428026 H. CHAO ET
AL:

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 773 648 B1

Description

[0001] The present invention relates to a method for use in a switching network which includes a plurality of switching nodes with switching node terminations for associating in a switching node termination internal header information to external header information as described in the preamble of claim 1, to a switching node termination realizing said method as described in the preamble of claim 5 and to a switching node and a switching network including this switching node termination as described in claims 9 and 10 respectively.

[0002] Such a method and a switching node termination realizing the latter method are already known in the art, i.e. from the article '*Design and Technology Aspects of VLSI's for ATM Switches*', written by Thomas R. Ban- niza, Gert J. Eilenberger, Bart Pauwels And Y. Therasse and published in *IEEE Journal on selected areas in communication*, Vol. 9, No 8, October 1991 from page 1255 to page 1264. As described in paragraph III.B of this article a termination link board, which is similar to the switching node termination of the present invention, and which is included in this multipath selfrouting switching network performs the conversion between multislot cells, i.e. data packets used internally in the switching network, and ATM cells, i.e. data packets used externally to the switching network. More specific, in paragraph IV.B.4, a TMC-out VLSI, included in the switching node termination uses an internal reference number included in the internal header information of the multislot cell to access the external header information of the ATM cell. The internal reference number is equivalent to the connection reference number mentioned in the preamble of claims 1, 5, 9 and 10 and identifies an internal connection within the switching node.

[0003] Although it is not explicitly mentioned in the article, it is obvious for a person skilled in the art that the earlier mentioned association will be mostly realised by means of an association table.

[0004] The connection reference number associated to an unicast connection is managed by the destination termination link board where the unicast connection is ending. On the contrary since, the connection reference number associated to a multicast connection is the same number for all destination termination link boards where the multicast connection is ending, the multicast connection reference numbers are managed centrally. Blocking occurs when a common multicast connection reference number can not be found free at all the multicast destination termination link boards. To avoid the latter blocking which is a result of the different ways of managing connection reference numbers for different types of transfer, the association table could be divided into two subranges : a unicast subrange and a multicast subrange, with the size of both ranges the same for all destination termination link boards.

[0005] However, such a partitioning between unicast and multicast would make the number of unicast con-

nections that can be ending on a destination termination link board directly dependent of the number of multicast connections, even if the probability that a multicast connection would terminate on all destination termination link boards is very low. As a result this relationship would reduce the amount of potential unicast connections on the destination termination link board to the size of the unicast subrange and would reduce the number of multicast connections within the multipath selfrouting switching network to the size of the multicast subrange.

[0006] An object of the present invention is to provide a method for enabling the above association and a network node termination realizing this method, such as the known one but which does not have the above drawback, i.e. in which there is no relationship between the different kinds of transfer type of the internal connections used inside the switching network and the external header information of the outgoing external connections.

[0007] According to the invention this object is achieved by the method described in claim 1 which is realized by the switching node termination described in claim 5 and with the switching node and the switching network described in claim 9 and 10 respectively.

[0008] Indeed, by using an additional association table, similar to the first association means to associate, based on the transfer type, the connection reference number to a transfer type independent connection reference number which is locally managed by the switching node termination and by using this transfer type independent connection reference number to access the external header information, a decoupling is realised between the different kinds of transfer type and the external header information, i.e. the external header information is obtained in a way which is independent of the different kinds of transfer type of the internal connections.

[0009] As a result thereof the maximum amount of potential unicast connections ending on a destination termination link board is only limited by the maximum number of possible connections ending on the destination termination link board itself and the maximum amount of potential multicast connections within a multipath selfrouting switching network is only limited by the size of the additional association table which can be bigger than the size of the maximum possible connections ending on a destination termination link board. To be noted that an additional association table has to be foreseen for each transfer type.

[0010] A possible way of realizing step a of the present method is to make use of a transfer pattern code included in the internal header information which identifies the type of transfer. This is described in claim 2 and claim 6.

[0011] To reduce the number of different kinds of connection reference numbers, the connection reference numbers which are associated to unicast transfer, i.e. a type of transfer using point - to - point connections, are

used as transfer type independent connection reference number. This can be done because the allocation of the unicast connection reference numbers is also managed locally by the switching node termination. This feature is described in claims 3 and 7.

[0012] A further feature of the present invention is that one of the different transfer types is a multicast transfer or point - to - multipoint connections. This is described in the claims 4 and 8.

[0013] . The above mentioned and other objects and features of the invention will become more apparent and the invention itself will be best understood by referring to the following description of an embodiment taken in conjunction with the accompanying drawing representing a switching node termination SNT adapted to associate internal header information IHI to external header information EHI according to the invention.

[0014] First, a functional description of the blocks shown in the figure will be given. Based on this description, implementation of the functional blocks in the figure will be obvious to a person skilled in the art. In addition, the method of the invention, i.e. the working of the switching node termination SNT will be described in further detail.

[0015] The embodiment, shown in the figure is used in a switching node of a switching network over which data packets are transferred. The internal header information IHI, included in an internal data packet received by the switching node termination, identifies an internal connection within the switching node which is ending in the switching node termination. The external header information EHI, included in an external data packet, identifies an outgoing external connection of the switching node which is originating from the switching node termination. The internal header information IHI includes a connection reference number CRN and a transfer type is associated to each internal connection. Such a type is for instance an unicast type connection, i.e. a type of transfer using point - to - point connections or a multicast type connection, i.e. a type of transfer using point - to multipoint connections.

[0016] The embodiment shown in the figure includes a determination module DETMOD, a first association circuit ASSCC1 and a second association circuit ASSCC2.

[0017] The determination module DETMOD is provided to determine the transfer type of the internal connection. Since the internal header information IHI, applied to this block, includes a transfer pattern code which characterizes the transfer type of the internal connection, the necessary information to determine the transfer type is available and is used. Interpretation means to interpret the transfer pattern code and to determine the transfer type are included in the determination module DETMOD.

[0018] It has to be remarked that, although the use of this transfer pattern code is mentioned in this preferred embodiment to determine the transfer type, it will be ob-

vious to a person skilled in the art that the invention is not restricted to switching node terminations SNT wherein the interpretation of this transfer pattern code is applied.

[0019] The first association circuit ASSCC1 is included to associate based on the transfer type the connection reference number CRN to a transfer type independent connection reference number TTI-CRN. In this first association circuit ASSCC1 the connection reference number CRN is used to get access to the transfer type independent connection reference number TTI-CRN via a transfer type specific table. In the drawing only the transfer type specific table for multicast transfer MC is shown.

[0020] It has to be noted here that because the connection reference numbers of multicast connections are identifying a multicast connection which is ending on different switching node terminations, these connection reference numbers are managed centrally in the network. But the transfer type independent connection reference numbers are identifying internal connections which are ending on a particular switching node termination i.e. a branch of a multicast connection ending on this switching node termination. Therefore, these transfer type independent connection reference numbers are managed, locally, by the switching node termination.

[0021] As already mentioned before, to reduce the number of different kinds of connection reference numbers, the transfer type independent connection reference number corresponds to the connection reference number associated to the unicast transfer, which is also managed, locally, by the switching node termination.

[0022] It has to be remarked that, although the connection reference number of unicast transfer is used in this embodiment as transfer type independent connection reference number, the present invention is not restricted to switching node terminations wherein such a choice is made.

[0023] The second association circuit ASSCC2 is included to associate the transfer type independent connection reference number TTI-CRN to the external header information EHI. The transfer type independent connection reference number TTI-CRN is used to get access to the external header information EHI, making use of a transfer table.

[0024] The principle working of the switching node termination SNT will be explained in the following paragraph with respect to unicast and multicast transfer, the working with respect to other types of transfer being identical.

[0025] It has to be noted that although in this preferred embodiment the working for two different transfer types is described : unicast transfer and multicast transfer, the different types of transfer within the switching node of the invention are not restricted to these two types.

[0026] An internal data packet, identifying an internal connection within the switching node, is received by the switching node termination SNT.

[0027] During the first step, the transfer pattern code included in the internal header information IHI which is included in this data packet is used by the determination module DETMOD to determine the transfer type of the internal connection.

[0028] During the second step and in case that the transfer type was determined as multicast transfer the connection reference number CRN, also included in the internal header information IHI, is associated to the transfer type independent connection reference number TTI-CRN by the first association circuit using the transfer type dependent table for multicast transfer MC.

[0029] Also during the second step but in case that the transfer type was determined as unicast transfer the connection reference number CRN of the unicast transfer, used as transfer type independent connection reference number TTI-CRN, is associated to the transfer type independent connection reference number TTI-CRN, to say, to itself.

[0030] During the third step the transfer type independent connection reference number TTI-CRN is associated by the second association circuit ASSCC2 to the external header information EHI, thereby identifying an outgoing external connection external to the switching node and originating from the switching node termination.

[0031] While the principles of the invention have been described above in connection with specific apparatus, it is to be clearly understood that this description is made only by way of example and not as a limitation on the scope of the invention.

Claims

1. A method for use in a switching network over which data packets are transferred and which includes a plurality of switching nodes with switching node terminations (SNT), and for associating in each one of said switching node terminations (SNT) internal header information (IHI) included in an internal data packet received by one of said switching node terminations and identifying an internal connection within said switching node and ending in said one switching node termination, to external header information (EHI) included in an external data packet and identifying an outgoing external connection external to said switching node and originating from said switching node termination, said internal header information including a first connection reference number (CRN) and a transfer type associated to said internal connection, **characterized in that** said method comprises the steps of:

- a. determining said transfer type;
- b. associating to said first connection reference number (CRN) based on said transfer type a second connection reference number

(TTI-CRN) which is internal to said one switching node termination (SNT);

c. associating to said second connection reference number said external header information (EHI).

2. A method according to claim 1, **characterized in that** said transfer type is **characterized by** a transfer pattern code included in said internal header information, step a of said method being realized by interpreting said transfer pattern code.

3. A method according to claim 1 or claim 2, **characterized in that** said first connection reference number being associated to a unicast transfer constitutes said second connection reference number (TTI-CRN);

4. A method according to claim 1,2, or claim 3, **characterized in that** said transfer type is a multicast transfer type.

5. A switching node termination (SNT) included in a switching node of a switching network over which data packets are transferred, said switching node termination (SNT) being adapted to associate internal header information (IHI) included in an internal data packet received by said switching node termination (SNT) and identifying an internal connection within said switching node and ending in said switching node termination, to external header information (EHI) included in an external data packet and identifying an outgoing external connection external to said switching node and originating from said switching node termination (SNT), said internal header information (IHI) including a first connection reference number (CRN) and a transfer type associated to said internal connection, **characterized in that** said switching node termination (SNT) includes:

a. determination means (DETMOD) to determine said transfer type;

b. first association means (ASSCC1) to associate based on said transfer type said first connection reference number (CRN) to a second connection reference number (TTI-CRN) which is internal to said switching node termination (SNT);

c. second association means (ASSCC2) to associate to said second connection reference number said external header information (EHI).

6. A switching node termination (SNT) according to claim 5, **characterized in that** said transfer type is **characterized by** a transfer pattern code included in said internal header information (IHI) and that said determination means include interpretation

means to interpret said pattern code and to thereby determine said transfer type.

7. A switching node termination (SNT) according to claim 5 or claim 6, **characterized in that** said first connection reference number associated to a unicast transfer constitutes said second connection reference number (TTI-CRN). 5
8. A switching node termination (SNT) according to claim 5, 6 or claim 7, **characterized in that** said transfer type is a multicast transfer type. 10
9. A switching node **characterized in that** said switching node includes a switching node termination (SNT) according to claim 5. 15
10. A switching network **characterized in that** said switching network includes at least one switching node termination (SNT) as described in claim 5. 20

Patentansprüche

1. Ein Verfahren zur Verwendung in einem Vermittlungsnetz, über das Datenpakete übertragen werden, und dass eine Vielzahl von Vermittlungsknoten mit Vermittlungsknoten-Abschlüssen (SNT) enthält, und, um in jedem der Vermittlungsknoten-Abschlüsse (SNT) interne Kopfinformation (IHI), die in einem internen Datenpaket enthalten ist, das von einem der Vermittlungsknoten-Abschlüsse empfangen wird und eine interne Verbindung in dem Vermittlungsknoten kennzeichnet und in dem Vermittlungsknoten-Abschluss endet, externer Kopfinformation (EHI) zuzuordnen, die in einem externen Datenpaket enthalten ist und eine abgehende externe Verbindung kennzeichnet, die für den Vermittlungsknoten extern ist und von dem Vermittlungsknoten-Abschluss kommt, wobei die interne Kopfinformation eine erste Verbindungs-Referenznummer (CRN) und einen der internen Verbindung zugeordneten Übertragungstyp enthält, **dadurch gekennzeichnet, dass** das Verfahren folgende Schritte umfasst: 25 30 35 40 45
 - a. Bestimmung des Übertragungstyps;
 - b. Auf der Grundlage des Übertragungstyps Zuordnung einer zweiten Verbindungs-Referenznummer (TTI-CRN), die für den Vermittlungsknoten-Abschluss (SNT) intern ist, zu einer ersten Verbindungs-Referenznummer (CRN);
 - c. Zuordnung der externen Kopfinformation (EHI) zur zweiten Verbindungs-Referenznummer; 50 55
2. Ein Verfahren gemäß Anspruch 1, **dadurch ge-**

kennzeichnet, dass der Übertragungstyp durch einen Übertragungs-Muster-Code gekennzeichnet ist, der in der internen Kopfinformation enthalten ist, wobei Schritt a des Verfahrens durch Interpretation des Übertragungs-Muster-Codes realisiert wird.

3. Ein Verfahren gemäß Anspruch 1 oder Anspruch 2, **dadurch gekennzeichnet, dass** die erste Verbindungs-Referenznummer, die einer Einfachverbindungs-Übertragung zugeordnet ist, die zweite Verbindungs-Referenznummer (TTI-CRN) bildet;
4. Ein Verfahren gemäß Anspruch 1, 2 oder Anspruch 3, **dadurch gekennzeichnet, dass** der Übertragungstyp ein Mehrfachverbindungs-Übertragungstyp ist.
5. Ein Vermittlungsknoten-Abschluss (SNT), der in einem Vermittlungsknoten eines Vermittlungsnetzes enthalten ist, über das Datenpakete übertragen werden, wobei der Vermittlungsknoten-Abschluss (SNT) so angepasst ist, dass er interne Kopfinformation (IHI), die in einem internen Datenpaket enthalten ist, das vom Vermittlungsknoten-Abschluss (SNT) empfangen wird und eine interne Verbindung innerhalb des Vermittlungsknotens kennzeichnet und im Vermittlungsknoten-Abschluss endet, externer Kopfinformation (EHI) zuordnet, die in einem externen Datenpaket enthalten ist und eine abgehende externe Verbindung, die für den Vermittlungsknoten extern ist und vom Vermittlungsknoten-Abschluss (SNT) ausgeht, kennzeichnet, wobei die interne Kopfinformation (IHI) eine erste Verbindungs-Referenznummer (CRN) und einen Übertragungstyp enthält, der jeder internen Verbindung zugeordnet ist, **dadurch gekennzeichnet, dass** der Vermittlungsknoten-Abschluss (SNT) folgendes enthält:
 - a. Bestimmungs-Mittel (DETMOD), um den Übertragungstyp zu bestimmen;
 - b. Erste Zuordnungs-Mittel (ASSCC1), um auf der Grundlage des Übertragungstyps die erste Verbindungs-Referenznummer (CRN) einer zweiten Verbindungs-Referenznummer (TTI-CRN) zuzuordnen, die für den Vermittlungsknoten-Abschluss (SNT) intern ist;
 - c. Zweite Zuordnungs-Mittel (ASSCC2), um der zweiten Verbindungs-Referenznummer die externe Kopfinformation (EHI) zuzuordnen.
6. Ein Vermittlungsknoten-Abschluss (SNT) gemäß Anspruch 5, **dadurch gekennzeichnet, dass** der Übertragungstyp durch einen Übertragungs-Muster-Code charakterisiert ist, der in der internen Kopfinformation (IHI) enthalten ist und dass die Bestimmungs-Mittel Interpretations-Mittel enthalten, um den Muster-Code zu interpretieren und dadurch

den Übertragungstyp zu bestimmen.

7. Ein Vermittlungsknoten-Abschluss (SNT) gemäß Anspruch 5 oder Anspruch 6, **dadurch gekennzeichnet, dass** die erste Verbindungs-Referenznummer, die einer Einfachverbindungs-Übertragung zugeordnet ist, die zweite Verbindungs-Referenznummer (TTI-CRN) bildet. 5
8. Ein Vermittlungsknoten-Abschluss (SNT) gemäß Anspruch 5, 6 oder Anspruch 7, **dadurch gekennzeichnet, dass** der Übertragungstyp ein Mehrfachverbindungs-Übertragungstyp ist. 10
9. Ein Vermittlungsknoten, **dadurch gekennzeichnet, dass** der Vermittlungsknoten einen Vermittlungsknoten-Abschluss (SNT) gemäß Anspruch 5 enthält. 15
10. Ein Vermittlungsnetz, **dadurch gekennzeichnet, dass** das Vermittlungsnetz mindestens einen Vermittlungsknoten-Abschluss (SNT) enthält, wie in Anspruch 5 beschrieben. 20

Revendications

1. Procédé à utiliser dans un réseau de commutation sur lequel des paquets de données sont transférés et qui comprend une pluralité de noeuds de commutation avec des terminaisons de noeud de commutation (en anglais « Switching Node Termination » - SNT), et pour associer dans chacune de ces terminaisons de noeud de commutation (en anglais « Switching Node Termination » - SNT) des informations d'en-tête internes (en anglais « Internal Header Information » - IHI) incluses dans un paquet de données interne reçu par l'une desdites terminaisons de noeud de commutation et identifiant une connexion interne dans ledit noeud de commutation et terminant dans ladite terminaison de noeud de commutation, à des informations d'en-tête externes (en anglais « External Header Information » - EHI) incluses dans un paquet de données externe et identifiant une connexion externe sortante vers ledit noeud de commutation et provenant de ladite terminaison de noeud de commutation, lesdites informations d'en-tête internes comprenant un premier numéro de référence de connexion (en anglais « Connection Reference Number » - CRN) et un type de transfert associé à ladite connexion interne, **caractérisé en ce que** ledit procédé comprend les étapes consistant à : 30
 - a. déterminer ledit type de transfert ; 35
 - b. associer audit premier numéro de référence de connexion (en anglais « Connection Reference Number » - CRN) sur la base dudit type 40

de transfert, un deuxième numéro de référence de connexion (TTI-CRN) qui est interne à ladite terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) ; c. associer audit deuxième numéro de référence de connexion lesdites informations d'en-tête externes (en anglais « External Header Information » - EHI).

2. Procédé selon la revendication 1, **caractérisé en ce que** ledit type de transfert est **caractérisé par** un code de motif de transfert inclus dans lesdites informations d'en-tête internes, l'étape a dudit procédé étant réalisée en interprétant ledit code de motif de transfert. 15
3. Procédé selon la revendication 1 ou 2, **caractérisé en ce que** ledit premier numéro de référence de connexion associé à un transfert à diffusion individuelle constitue ledit deuxième numéro de référence de connexion (TTI-CRN). 20
4. Procédé selon la revendication 1, 2 ou 3, **caractérisé en ce que** ledit type de transfert est un type de transfert à multidiffusion. 25
5. Terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) incluse dans un noeud de commutation d'un réseau de commutation sur lequel des paquets de données sont transférés, ladite terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) étant adaptée pour associer des informations d'en-tête internes (en anglais « Internal Header Information » - IHI) incluses dans un paquet de données interne reçu par ladite terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) et identifiant une connexion interne dans ledit noeud de commutation et terminant dans ladite terminaison de noeud de commutation, à des informations d'en-tête externes (en anglais « External Header Information » - EHI) incluses dans un paquet de données externe et identifiant une connexion externe sortante vers ledit noeud de commutation et provenant de ladite terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT), lesdites informations d'en-tête internes (en anglais « Internal Header Information » - IHI) comprenant un premier numéro de référence de connexion (en anglais « Connection Reference Number » - CRN) et un type de transfert associé à ladite connexion interne, **caractérisée en ce que** ladite terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) comprend : 35
 - a. des moyens de détermination (DETMOD) pour déterminer ledit type de transfert ; 40

a. des moyens de détermination (DETMOD) pour déterminer ledit type de transfert ;

- b. des premiers moyens d'association (ASSCC1) pour associer sur la base dudit type de transfert ledit premier numéro de référence de connexion (en anglais « Connection Reference Number » - CRN) à un deuxième numéro de référence de connexion (TTI-CRN) qui est interne à ladite terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) ; 5
- c. des deuxièmes moyens d'association (ASSCC2) pour associer audit deuxième numéro de référence de connexion lesdites informations d'en-tête externes (en anglais « External Header Information » - EHI). 10

6. Terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) selon la revendication 5, **caractérisée en ce que** ledit type de transfert est **caractérisé par** un code de motif de transfert inclus dans lesdites informations d'en-tête internes (en anglais « Internal Header Information » - IHI) et en ce que lesdits moyens de détermination incluent des moyens d'interprétation pour interpréter ledit code de motif et pour ainsi déterminer ledit type de transfert. 15 20 25
7. Terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) selon la revendication 5 ou 6, **caractérisée en ce que** ledit premier numéro de référence de connexion associé à un transfert à diffusion individuelle constitue ledit deuxième numéro de référence de connexion (TTI-CRN). 30
8. Terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) selon la revendication 5, 6 ou 7, **caractérisée en ce que** ledit type de transfert est un type de transfert à multidiffusion. 35 40
9. Noeud de commutation **caractérisé en ce que** ledit noeud de commutation inclut une terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) selon la revendication 5. 45
10. Réseau de commutation **caractérisé en ce que** ledit réseau de commutation inclut au moins une terminaison de noeud de commutation (en anglais « Switching Node Termination » - SNT) selon la revendication 5. 50

55

